

I. IDENTIFICATION

Product identification used on label
Product Name:
Product Identifier:
Recommended Use of the
Chemical and restrictions on use:

MAXI-BATTERY PROFESSIONAL WATERMELON Battery, Still, Electric Liquid Odor Counteractant

Company:	AIR-SCENT INT'L
	RIDC INDUSTRIAL PARK
	290-298 ALPHA DRIVE
	PITTSBURGH, PA 15238
Emergency Phone	EMERGENCY PHONE: (800) 535-5053
Number:	INFORMATION PHONE: 800-247-0770
	INFORMATION FAX: 412-252-1010
	IF SWALLOWED CALL YOUR POISON
	CONTROL CENTER AT 1-800-222-1222

II. HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with paragraph (d) of §1910.1200;



GHS Classification:	Skin Corrosion/Irritation Category 2; Flammable Liquid Category 4
GHS Signal Word:	Warning
GHS Hazard	Cumbustible Liquid; Causes skin irritation.
GHS Precautions:	
Safety Precautions:	Keep away from open flames. No smoking. Wash thoroughly after handling. Wear protective gloves, eye protection/face protection.
First Aid Measures:	IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire:
Storage:	Store in a well-ventilated place. Keep cool.
Disposal:	Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

III. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	%
Hydrotreated light distillate (Petroleum)	64742-47-8	60 - 99
2-propanol	67-63-0	1 - 5

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret is required.

IV. FIRST-AID MEASURES

IV. TINGT AID WIEASONES			
Inhalation:	Remove to	fresh air. If breathing is difficult, have a trained individual administer	
	oxygen. If r	not breathing, give artificial respiration and have a trained individual	
	administer	oxygen. Get medical attention immediately.	
Eyes:	Immediate	ly flush eyes with plenty of water for at least 20 minutes retracting	
	eyelids ofte	en. Tilt the head to prevent chemical from transferring to the	
	uncontami	nated eye. Get immediate medical attention and monitor the eye daily	
	as advised	by your physician.	
Skin Contact:	Wash with	soap and water. Remove contaminated clothing and launder. Get	
		tention if irritation develops or persists.	
Ingestion:		uce vomiting and seek medical attention immediately. Drink two glasses	
	of water or	milk to dilute. Provide medical care provider with this MSDS. Induce	
		s a last measure. Induced vomiting may lead to aspiration of the material	
		ngs potentially causing chemical pneumonitis.	
Most important			
symptoms and effects -	No Data Av	<i>r</i> ailable	
acute			
Most important			
symptoms and effects -	No Data Av	<i>r</i> ailable	
chronic			
Notes to Doctor:	No additior	nal first aid information available	
V. FIRE FIGHTING MEASURE	S		
Flammability Summary:		Combustible	
Extinguishing Media:		Use alcohol resistant foam, carbon dioxide, or dry chemical	
		extinguishing agents. Water may be ineffective but water spray can	
		be used extinguish a fire if swept across the base of the flames.	
		Water can absorb heat and keep exposed material from being	
		damaged by fire. Alcohol foam Dry chemical Carbon dioxide	
Extinguishing Media advise	ed against:	No Data Available	
Fire and/or Explosion Hazards:		Vapors may be ignited by sparks, flames or other sources of ignition	
		if material is above the flash point giving rise to a fire (Class B).	
		Vapors are heavier than air and may travel to a source of ignition and	
		flash back. Combustible Liquid. Can form explosive mixtures at	
		temperatures at or above the flash point.	
		Empty containers that retain product residue (liquid, solid/sludge, or	
		vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder,	
		drill, grind, or expose container to heat, flame, sparks, static	
		electricity, or other sources of ignition. Any of these actions can	
		potentially cause an explosion that may lead to injury or death.	

Fire Fighting Methods and Protection:	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.
Hazardous Combustion Products: VI. ACCIDENTAL RELEASE MEASURES	Carbon dioxide, Carbon monoxide, Toxic fumes., Toxic gases
Methods for Clean-up:	No health affects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section VIII of this MSDS No special spill clean-up considerations. Collect and discard in regular trash.
VII. HANDLING AND STORAGE	
Handling Technical Measures and Precau	with all chemicals, good industrial hygiene practices should be followed when handling this material. Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Wash thoroughly after handling Do not get in eyes, on skin and clothing Ground and bond containers when transferring material "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Use spark-proof tools and explosion-proof equipment Keep in air-tight containers- material is hygroscopic. Remove
Storage Technical Measures and Condition	Keep container closed when not in use Store in a cool dry place Keep away from heat, sparks, and flame Keep away from sources of ignition Store in a tightly closed container

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures:	Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Ventilation is required to maintain operator exposure below published exposure limits. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits Explosion proof exhaust ventilation should be used.
Respiratory Protection:	Respiratory protection will be required when handling this product. Use respirators only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator. Wear a NIOSH approved respirator if any exposure is possible.

MAXI-BATTERY PROFESSIONAL WATERMELON

Page 3 of 7

Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available. Wear goggles and a Face shield
Skin Protection:	Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work Where contact is likely, wear chemical resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield
Gloves:	No information available
Handling Instructions:	As with all chemicals, good industrial hygiene practices should be followed when handling this material. Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Wash thoroughly after handling Do not get in eyes, on skin and clothing Ground and bond containers when transferring material "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Use spark-proof tools and explosion-proof equipment Keep in air-tight containers- material is hygroscopic. Remove contaminated clothing and wash before reuse

mg/m3 TWA

Control Parameters: ACGIH TLV-TWA ACGIH STEL Chemical Name 100 ppm TWA; 525 mg/m3 TWA 100 ppm TWA; 983) (500) ppm STEL; (1230)

IX. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Clear
Odor:	Mild Comparable to Standard
Odor Threshold:	ND
pH:	Not Available
Flash Point:	165 º F
Evaporation Rate:	Not Available
Flammability (Solid, Gas):	No Data Available
Upper Flammable/Explosive Limit:	6.0
Lower Flammable/Explosive Limit:	1.1
Vapor Density:	>1
Relative Density:	1
Solubility in Water:	Soluble in water- No
Octanol/Water Partition Coefficient:	0.14
Decomposition Temperature:	260
Volatiles, % by weight:	1
Volatiles, % by weight:	1
Bulk Density:	6.96

X. STABILITY AND REACTIVITY

Reactivity: Chemical Stability: Possibility of Hazardous Reactions: No Data Available Stable under normal conditions. No Data Available

MAXI-BATTERY PROFESSIONAL WATERMELON

OSHA PEL

mg/m3 TWA 400 ppm TWA; 980

mg/m3 TWA

mg/m3 STEL

500 ppm TWA; 2900

Conditions to Avoid:	None known. Contamination Elevated temperatures
Materials to Avoid/Chemical Incompatibility:	Strong oxidizing agents Amines Strong acids Caustics (bases)
	Acetic anhydride Strong reducing agents Chlorinated
	compounds
Hazardous Decomposition Products:	Carbon dioxide Carbon monoxide Toxic fumes. Toxic gases
Hazardous Decomposition Products:	•

XI. TOXICOLOGICAL INFORMATION

Routes of Entry: Most Important Symptoms:	Skin contact, Eye contact, l No Data Available	nhalation	
Target Organs Potentially Affected by Exposure: Chemical Interactions That Change Toxicity: Medical Conditions Aggravated by Exposure:		Eyes, Skin, Respiratory Tract None Known	
		Eye disease, Skin disease including eczema and sensitization, Respiratory disease including asthma and bronchitis	
Immediate (Acute) He	alth Effects by Route of Expos	ure:	
Inhalation Irritatio	n: Can cause r	espiratory irritation.	
Skin Contact:	Can cause n permanent	noderate skin irritation, defatting, and dermatitis. Not likely to cause damage.	
Eye Contact:	Can cause n injure eye ti	noderate irritation, tearing and reddening, but not likely to permanently issue.	
Ingestion Irritation	-	mouth, throat, and stomach. Can cause abdominal discomfort, nausea, d diarrhea. Aspiration of material into the lungs can cause chemical s.	
Ingestion Toxicity:	Harmful if s	wallowed.	
Long-Term (Chroni	c) Health Effects:		
Carcinogenicity:	None of the	substances have been shown to cause cancer in long term animal	
	studies. Not	a carcinogen according to NTP, IARC, or OSHA.	
Reproductive toxic	i ty: No data ava	ilable to indicate product or any components present at greater than	
	0.1% may ca	ause birth defects.	
Germ cell mutagen	-	ilable to indicate product or any components present at greater than agenic or genotoxic.	

	5 5
Inhalation:	Upon prolonged and/or repeated exposure, can cause severe respiratory irritation,
	dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.
Skin Contact:	Upon prolonged or repeated contact, can cause moderate skin irritation, defatting,
	and dermatitis. Not likely to cause permanent damage.

Component Toxicology Data:		
Chemical Name	CAS Number	LD50/LC50
No data available		

Has the chemical been classified as a Carcinogen by NTP, IARC or OSHA.

Chemical Name	OSHA	IARC	NTP
	Carcinogen	Carcinogen	Carcinogen

MAXI-BATTERY PROFESSIONAL WATERMELON

	1			
No Data				
Available				
XII. ECOLOGICAL INFORMATIO	N			
Overview:	This material is not ex	pected to be harmfu	Il to the ecology	
Mobility in Soil:	No Data Available			
Persistence:	No Data Available			
Bioaccumulation:	No Data Available			
Other adverse effects	No Data Available			
Ecotoxicity Data				
Chemical Name	CAS Number	Aquatic EC50	Aquatic ERC50	Aquatic LC50 Fish
		Crustacea	Algae	
No Data Available				
XIII. DISPOSAL CONSIDERATIO	NS			
Waste Description for Spent I	Product: Spent or d	iscarded material ma	ay be a hazardous wa	ste.
Waste Description for Empty	No Data A	vailable		
Packaging:				
Disposal Methods:			ERS, ON THE GROUNI	
Disposal Methods:			practices must be in c	
			ocal laws and regulation	-
			Waste characterizat	-
	complianc	e with applicable law	s are the sole respon	sibility of the waste
	generator.	As your supplier, w	e have no control ove	er the management
			cesses of parties han	
			ented here pertains of	
			ing to this MSDS. For	
			preferred options incl ator or other thermal	
			cial agencies may hav	
			sportation, handling	-
	_	_	may not be covered in	-
	user shall	have to review these	regulations to ensure	e full compliance
	with all ap	plicable regulations.		
XIV. TRANSPORTATION INFOR	ΜΑΤΙΟΝ			
US DOT Ground Shipping Desc		icted		
IATA Shipping Description:	Not Restr			
IMDG Shipping Description:	Not Restr	icted		
XV. REGULATORY INFORMATIC TSCA Status All compone	ents in this product are	on the TSCA Invento	rv	
			• 3 •	
Chemical Name	CAS #	F	Regulation	% Range
MAXI-BATTERY PROFESSIO	ONAL WATERMELO	Ν	Ра	age 6 of 7

No 313-listed chemicals in this product

SARA 313

XVI. OTHER INFORMATION

Revision Date:	07/09/2015
Disclaimer:	Important: While the descriptions, data and information contained herein are presented in good faith and believed to be accurate, it is provided for your guidance only. Because many factors may affect processing or application/use, we recommend that you perform an assessment to determine the suitability of the product for your particular purpose prior to use. Nothing herein should be interpreted as a recommendation to infringe existing patents or violate any laws or regulations. No warranties of any kind, either expressed or implied, including fitness for a particular purpose are made regarding the product described. We assume NO responsibility for any injuries resulting from misuse or misapplication of this product or that might be sustained because of inhalation, ingestion, absorption or other contact with this product. In no case shall the descriptions, information, or data provided be considered a part of our terms and conditions of sale. Further, the descriptions, data and information furnished hereunder are given gratis. No obligation or liability for the description, data and information given are assumed. All such being given and accepted at your risk.
	and and methods of the decenter is a contract being Bren and decepted at your how